

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
7 October 2004 (07.10.2004)

PCT

(10) International Publication Number
WO 2004/086736 A1

(51) International Patent Classification⁷: **H04M 1/73**,
H04Q 7/32

(21) International Application Number:
PCT/IB2003/001155

(22) International Filing Date: 28 March 2003 (28.03.2003)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant (for all designated States except US): **TELEFONAKTIEBOLAGET LM ERICSSON (publ)**
[SE/SE]; S-164 83, Stockholm (SE).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **HAARTSEN, Jacobus, Cornelis** [NL/NL]; Bruchterweg 81, NL-7772 BG Hardenberg (NL).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:

(74) Agent: **WEATHERFORD, Sidney**; Ericsson Inc., 6300 Legacy, MS EVW 2-C-2, Plano, TX 75024 (US). — as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for all designations

[Continued on next page]

(54) Title: **METHOD AND APPARATUS FOR CALCULATING WHETHER POWER LEVEL IS SUFFICIENT FOR DATA TRANSFER**



(57) Abstract: A method and apparatus for managing traffic in a network to and from a remote communications device with limited power supply resources. A controller determines the existing power level of the device and uses the determination to control data transmission to and from the device. Data may be transmitted and received by the device by determining the power required to complete a transmission or reception. The controller then determines whether to send the data, redirect the data, cancel the data transmission, or transmit only a portion of the data. The decision is made as to which option to choose based on the amount of power available to complete the data transmission.



Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

METHOD AND APPARATUS FOR CALCULATING WHETHER POWER LEVEL IS SUFFICIENT FOR DATA TRANSFER.

FIELD OF THE INVENTION

5 This invention relates to wireless and wireline communication systems. In particular, this invention relates to wireless and wireline communication systems and the status of power sources associated with the communication systems. Even more particularly, this invention relates to battery powered portable units, mobile units and units located where wiring for power supply is difficult or non-
10 existent.

BACKGROUND OF THE INVENTION

 There has been incredible progress in wireless communications in the last few decades. The economic growth and progress in worldwide prosperity has
15 brought electronic and wireless applications into nearly everybody's reach. Cellular and mobile communications are a booming success. Portable devices, including mobile phones, can now be produced having acceptable cost, size and power consumption.

 Mobile phone communications for the consumer market started with a
20 phone system derived from the police and rescue services and was based on an analog technology improved and optimized in the seventies and eighties. These systems led to the first analog phone systems for public usage such as Advanced Mobile Phone Service (AMPS), Nordic Mobile Telephone (NMT) and Total Access Communications Systems (TACS). The usage of mobile phones really
25 took off in the nineties with the introduction of mobile phone systems based on digital technology like Global System for Mobile Communications (GSM), Digital Advanced Mobile Phone Service (D-AMPS) and Personal Digital Cellular (PDC). Although radio technology is focused mainly on voice communications (with respect to handheld radios) data services grow in importance and eventually a
30 mobile Internet will be established.

CONFIRMATION COPY

New systems based on packet data transmission are already planned and some are being deployed. Examples are GPRS (General Packet Radio Service) and UMTS (Universal Mobile Telephone System). Whereas cellular systems address wide area coverage, providing national services anywhere, other systems have been designed to give more localized services such as in an office or a residence. Today, indoor systems based on the WLAN IEEE 802.11 standard are widely deployed to provide high data-rate access in restricted areas. A competing system called HIPERLAN (High PERformance LAN) has been designed to complement the cellular systems like UMTS by providing high capacity and high data rates to slowly moving users in hotspot areas. For the cordless telephony at home, DECT (Digitally-Enhanced Cordless Telephony) has been standardized and is widely used in households in Europe.

Recently, a new air interface called Bluetooth was introduced to replace all cables between mobile phones, laptop computers, headsets, PDAs, and so on. An introduction to the Bluetooth system can be found in "BLUETOOTH – The universal radio interface for ad hoc, wireless connectivity," by J.C. Haartsen, Ericsson Review No. 3, 1998. Radio communication systems for personal usage differ importantly from radio systems like the public mobile phone network. In the latter systems, a licensed band is used which is fully controlled by the phone operator and procedures are implemented to guarantee an interference free channel. In contrast, personal radio communication equipment has to operate in an unlicensed band and has to deal with uncontrolled interference. A suitable band is the ISM (Industrial, Scientific and Medical) band at 2.45 GHz, which is globally available and provides 83.5 MHz of radio spectrum.

Bluetooth is a frequency hopping system which hops over 79 hop carriers in the ISM band with a nominal hop rate of 1600 hops/s. Bluetooth deploys a slotted channel with time slots of 625 μ s. Each slot uses a different hop carrier selected according to a pseudo-random hopping scheme. Bluetooth radio communications are based on peer communications and ad-hoc networking. This means that the system is not based on a hierarchical scheme with fixed

infrastructure of base stations and portable terminals that communicate with the base stations via radio signals as is common in cellular systems and WLAN systems. In peer communications, all units are equal. There is no centralized control that can for example take care of resource and connection management
5 and provide other support services.

In ad-hoc networks, any unit can establish a connection to any other unit in range. Ad-hoc networks are usually based on peer communications. To support the cable replacement scenarios as mentioned above, data traffic over a radio interface must be very flexible. The interface must support both symmetric and
10 asymmetric (in either direction) traffic flows and synchronous and asynchronous services. In Bluetooth, this has been realized with a very flexible slot structure without any multi-slot frames or anything alike. The time axis in Bluetooth is divided into slots, and the connected units are free to allocate the slots for transmission or reception.

15 Advances in wireless technology and the growing demand for more flexible applications provided by wireless communications makes it highly likely that this field will expand to provide greater information flow to and from other types of portable devices and fixed access points. More specifically, it is likely that further advances in technology will provide very inexpensive radio equipment, which can
20 be easily integrated into many devices. This will reduce the number of cables currently used and vastly expand the usage possibilities. However, large deployments of wireless applications would not have been possible without large improvements in battery technology.

Size reduction and capacity increase in batteries have tried to keep pace
25 with the size reduction and intensified processing in the wireless terminals. However, developments towards higher data rates and mobile services that require more intense data exchange as well as more advanced user presentation (like video) will put great pressure on the power supply provided by the batteries. In wireless systems, data rate and power consumption are different parameters of
30 the same equation. In all wireless communication systems, power management

functions are present to keep the power consumption to a minimum, leaving as much standby and talk time for the user as possible. It would be desirable to provide the status of a receiver's battery to a connected wireless system so as to optimize and improve the operation of the user's wireless terminal.

5 Wireless communication devices are attractive because of the freedom of movement they offer. However, this also means that the unit will be dependent upon batteries for power supply. Wireless applications are seen more and more as a replacement of the wired application, thus putting greater demands on transfer capacity and power consumption. Unfortunately, the progress in
10 advanced wireless applications is moving forward more quickly than the advances in battery technology. Therefore, research is taking place to look for other energy resources like fuel cells.

 In general, radio protocols include features that take into account the limited power resources in the mobile terminals. For example, in cordless and
15 cellular phone systems, low power modes are defined that keep the units locked to a beacon or control channel at a low duty cycle when there is no voice connection. In general, these power management functions try to keep the current drawn from the battery as low as possible.

 There are various examples of methods to monitor and conserve battery
20 power in wireless devices. For instance, U.S. Patent Number 6,459,896 issued to Liebenow et al., discloses a system and method for notifying a remote device of a low battery condition in a wireless communications system. A wireless, battery operated device may be attached to a network with a battery monitor installed in the wireless device. If the battery discharges to a predetermined power level,
25 without corrective action being taken, the battery monitor sends notification of the power level to a remote device. This notification may be a warning to the user of the remote device that the connection to the wireless device cannot be maintained due to low power level. The warning may be a pre-recorded announcement.

30 U.S. Patent Number 6,108,316 issued to Agrawal et al., discloses a

method for adapting scheduling priorities to conserve battery power in mobile terminals within a wireless communication system. A scheduling method is disclosed wherein a base station receives a signal from a mobile terminal that the terminal's battery level is below a predetermined threshold. The Base station may
5 reschedule transmissions to the mobile so that messages may have a higher probability of successful transmission before the battery power level diminished further.

Most, if not all, battery-driven equipment today has some method or apparatus of determining the battery or power source status of the equipment.
10 The above prior art examples relate to monitoring a wireless device battery and either notifying the device holder of a low battery condition or scheduling transmissions to attempt to transmit a complete message before the device battery expires. However, either example may allow a device to send a message that may not be completed. There is therefore a need in the art for a method and
15 apparatus in a wireless communication system to account for the power supply status of the (mobile) devices in the system. In other words, there is a need to manage traffic flows based on known power supply levels in the system.

SUMMARY OF THE INVENTION

20 To address the above-discussed deficiencies of the prior art, it is a primary objective of the present invention to provide a method and apparatus for managing a communication device power source for use in a network. A controller coupled to the network and the device determines the existing power level of the device's power source (battery). The controller uses the information to
25 control data transmission to and from the device while taking into account the power level of the power source. Data may be transmitted and received by the device by determining the power available to complete a transmission or reception. The controller then determines whether to transfer the data to the target, redirect the data, cancel the data transmission or transfer only a portion of
30 the data (to or from the communication device)

When a communication device is initially connected to a network, information regarding the device's power source and the manner in which the device drains power when in operation may be passed to a controller. This information is periodically updated. During an active connection, the current state
5 of the device's power source is determined and the device or the controller may calculate the drain rate of the power source as related to the services available and that the device is capable of handling.

When an incoming call (or outgoing call from the device) to the device is detected the size of the data to be transferred is determined. A calculation is
10 made to determine how much data may be transferred using the currently available power. Actions that may be taken by the present invention include: sending the complete transmission to a destination, sending a portion of the transmission to the destination and the remainder to a predetermined address and re-directing the entire transmission to a network address. When a data is re-
15 directed to an alternate address, a notification is sent to the recipient describing the actions taken.

Status of the power supply in each of the participating units in the network is determined. Based on the battery status of one unit, different actions in the network may take place. For example, the status of the power levels can
20 influence traffic scheduling in the network. In a cellular system, a central controller in the network can inform the mobile user that the current power level of the mobile phone's battery is insufficient to support a requested service. For instance, a connection is established between a user and a mobile unit for receiving a 1 MByte data file. The current battery level may be too low to
25 complete the entire transmission. If a control unit in the mobile network knows the battery status, the file transfer may be diverted to a mailbox in the network rather than send it over the air to the mobile unit. Simultaneously, it may signal to the mobile user that a file is waiting, but that the battery level is too low to support downloading the complete file.

30 The type of information sent to a mobile unit may also depend on its

battery status. For example, a PDA connects wirelessly to a Wireless Local Area Network (WLAN) to check Email. If the PDA battery power level is low only the Email headings are sent. Attachments and content of the email are kept within the central mailbox. The user is notified that attachments are waiting but the battery
5 has to be charged before more information can be retrieved.

In another embodiment, a large number of sensors may be connected wirelessly to a master control unit. This master unit polls the sensors at a very low duty cycle to obtain sensor readings. In these readings, the sensor may include the current battery status. If the battery is too low (for example to supply more
10 readings, or to remain in standby until the next poll event), the master unit may signal an alarm or other indication to replace or recharge the battery in that particular sensor.

In a peer-to-peer link as in Bluetooth connected devices, the battery status of one unit may affect the behavior of another unit. For example, if a headset that
15 is paired to a mobile phone has a battery level that is still sufficient to support the standby mode but not sufficient to support the talk mode, an incoming call may be directed to the speaker/microphone in the mobile phone rather than to the headset.

In an additional embodiment of the present invention the quality of service
20 offered to the mobile user may depend on the mobile's battery power level. For example, the power level may be sufficient to support either a 64 kb/s toll-quality speech connection for 10 seconds, or an 8 kb/s acceptable speech connection for 2 minutes. The system may select the latter as it will better serve the user under these conditions.

25 Future wireless systems will provide multi-media messaging. These messages may include voice, music, video, and more. Based on the battery level in the receiving device, the wireless system may decide to send only part of the message. For example, it may only send the voice message but not the video. It may indicate that an accompanying video is waiting but the battery has to be
30 replaced or recharged before this video can be downloaded.

In the present invention, the battery power level of the mobile as well as the power drain for the requested service is determined. In particular, a controller knows the power consumption per bit of transmitted or received data. With the power drain per bit and the battery level, it can be derived how many bits can still
5 be received, or alternatively, how long a service with a certain bit rate can be provided. The power consumption per bit may be dependent on the modulation mode (e.g. GSM or EDGE modulation) in the case of a mobile unit in a wireless network. The information about power drain per bit may be communicated to the network once (the controller may include a record with the unit's ID,
10 characteristics, features, and also the power consumption per mode). In addition, the current battery status and/or the power drain may also be communicated with regular updates since the power drain rate may change over time. Alternatively, the receiver can calculate the total number of bits it can receive based on the current battery power level and power drain and communicate that number to the
15 controller.

In general, battery management as disclosed in the present invention will prevent loss of connection in the middle of a transaction. Anticipating battery power levels will improve the user experience. By blocking a connection in the beginning and implementing alternatives for as long as the battery level is low is
20 better than being disconnected during the transaction due to loss of battery power.

The foregoing has outlined rather broadly the features and technical advantages of the present invention so that those skilled in the art may better understand the detailed description of the invention that follows. Additional
25 features and advantages of the invention will be described hereinafter that form the subject of the claims of the invention. Those skilled in the art should appreciate that they may readily use the conception and the specific embodiment disclosed as a basis for modifying or designing other structures for carrying out the same purposes of the present invention. Those skilled in the art should also
30 realize that such equivalent constructions do not depart from the spirit and scope

of the invention in its broadest form.

Before undertaking the DETAILED DESCRIPTION, it may be advantageous to set forth definitions of certain words and phrases used throughout this patent document: the terms "include" and "comprise," as well as derivatives thereof, mean inclusion without limitation; the term "or," is inclusive, meaning and/or; the phrases "associated with" and "associated therewith," as well as derivatives thereof, may mean to include, be included within, interconnect with, contain, be contained within, connect to or with, couple to or with, be communicable with, cooperate with, interleave, juxtapose, be proximate to, be bound to or with, have, have a property of, or the like; and the term "controller" means any device, system or part thereof that controls at least one operation, such a device may be implemented in hardware, firmware or software, or some combination of at least two of the same. It should be noted that the functionality associated with any particular controller may be centralized or distributed, whether locally or remotely. In particular, a controller may comprise one or more data processors, and associated input/output devices and memory that execute one or more application programs and/or an operating system program. Definitions for certain words and phrases are provided throughout this patent document, those of ordinary skill in the art should understand that in many, if not most instances, such definitions apply to prior, as well as future uses of such defined words and phrases.

BRIEF DESCRIPTION OF THE DRAWINGS

The disclosed invention will be described with reference to the accompanying drawings, which show important exemplary embodiments of the invention and which are incorporated in the specification hereof by reference, wherein:

Figure 1 depicts a mobile phone display with battery indication (prior art);

Figure 2 illustrates a cellular phone system utilizing battery management in accordance with the present invention;

Figure 3 depicts a cordless phone system including battery management according to the present invention;

Figure 4 illustrates a timing diagram of parameters encountered in cordless phone operation as depicted in Figure 3;

5 Figure 5 depicts a sensor system with battery management according to the present invention;

Figure 6 illustrates a Bluetooth connection between PC and PDA with battery management according to the present invention;

10 Figure 7 depicts a Bluetooth connection between a mobile phone and a paired headset with battery management according to the present invention; and

Figure 8 illustrates a method for managing a communication device power source in a network according to a preferred embodiment of the present invention.

15 **DETAILED DESCRIPTION OF THE INVENTION**

The numerous innovative teachings of the present application will be described with particular reference to the presently preferred exemplary embodiments. However, it should be understood that this class of embodiments provides only a few examples of the many advantageous uses of the innovative teachings herein. In general, statements made in the specification of the present application do not necessarily delimit any of the various claimed inventions. Moreover, some statements may apply to some inventive features or embodiment(s) but not to others.

In Figure 1, the display of a mobile phone is shown with a battery level indicator in the lower right corner. Battery indicator 105 shows the power level of the battery (not shown). When the power level of the battery is very low the phone may sound an audible signal or maybe initiate a flashing light that alarms the user who can then replace or re-charge the battery. However, the power drain on the battery is different for different services. For example, a phone with a full battery may have a 7-day standby time or a 4 hours talk time. If the battery is 5%

25 30

filled, mobile phone 100 can remain in standby for another 8 hours. However, when accepting a call during this time frame, the duration of the voice connection quickly drops to 12 minutes or less. With more demanding services like video and multi-media messages, the imbalance becomes even larger. As a result, communications may be disrupted in the middle of a transaction since the battery level may have been adequate when transmission started, but was not high enough to support the entire transaction.

A battery management function is disclosed that takes into account a power level of the battery and the expected power drain in the battery accompanying the service provided or requested. In the present invention, the power level status of the battery is not only known inside the terminal in which the battery is residing (as in the phone in Figure 1), but may be communicated wirelessly to a control center in the network and to other wireless units connected to the network. Obviously, in the case of a wireless network, the power level status may be communicated wirelessly.

Figure 2 illustrates a cellular phone system utilizing battery management according to the present invention. Cellular system 200 includes macro-cellular base station 210, micro-cell base station 220, base station controller (BSC) 230, server 240 and terminal 205. As illustrated, terminal 205 is out of the range of micro-cell base station 220 and is locked in standby or idle mode to base station 210 via cellular link 208. A multimedia (MM) message with voice and video content may be sent from network 250 to terminal 205. Terminal 205 is assigned to a traffic channel.

Prior to beginning any transaction, terminal 205 reports its battery status to BSC 230. Based on the battery status report, BSC 230 will make a choice: if the battery status is high, BSC 230 will forward the MM message to terminal 205 or if the battery status is really low, BSC 230 will divert the MM message to a mailbox for terminal 205. Simultaneously, a short-message-service (SMS) message is sent to terminal 205 to announce that an MM message is available in the network but that the battery is too low to allow delivery. However, the battery level may be

high enough to only send the voice content of the message. BSC 230 may then send the voice content of the message to terminal 205 and divert the video content to the mailbox of the user.

In another example, terminal 205 may need to transmit an Email message via communications network 200. Terminal 205 contacts base station 210 for a traffic channel. Based on the 1) size of the Email message, 2) the transmit power required to overcome path loss between base station 210 and terminal 205, and 3) the battery status, terminal 205 and/or base station 210 may decide to postpone transmission. Preferably, network 200 (e.g. in the BSC or some other control unit) utilizes all this information to make a decision. When terminal 205 moves into the direction of micro-cell base station 220, the idle connection between terminal 205 and base station 210 is handed over to micro-cell base station 220. BSC 230, recognizing that terminal 205 is now connected to the micro-cell base station with a much shorter range, may allocate a traffic channel between micro-cell base station 220 and terminal 205 to transfer the email. Since the distance is much smaller and path loss is lower, the battery level may be sufficient to effect complete transfer of the Email message. The user is of course not involved in this activity as it happens in the background.

In addition to battery level, terminal 205 may provide the anticipated power drain (either per bit or per second) for the considered service. This power drain may be constant (e.g. for terminals without transmit power control and a fixed modulation format) in which case terminal 205 only has to communicate once to network 200. This type of information may be stored in database 260 where a record is kept of the terminal equipment that is connected to network 200. For example, each record may be labeled by the IMEI (International Mobile Equipment Identity) or some other serial number associated with terminal 205. The record can further include services, modes and additional features that terminal 205 can support. The power drain per mode can also be incorporated in this record. Alternatively, at connection establishment, terminal 205 can directly provide the server with information about the amount of data that can be

transferred or the service time that is supported by the current battery status.

The power drain may also change over time. For example, when terminal 205 is communicating with BSC 230, terminal 205 may move away from BSC 230. Cellular systems usually include power control to compensate for the increase in
5 signal attenuation. Consequently, terminal 205 will be ordered to increase transmit power resulting in an increased power drain. An update of the power drain can, for example, be signaled to BSC 230 via the slow-associated control channel (SACCH), which may result in further actions in the network to optimize the traffic flow.

10 In the example above, terminal 205 may be located in a macro-cell at quite a distance from the base station. Transmit power of terminal 205 may be controlled at 200 milliwatts (mW) for acceptable reception by the base station. The current drain to support a 50 kilobits per second (kb/s) GPRS uplink connection is 100mA. The current battery level of terminal 205 is at 10mAh.
15 Therefore this service can be maintained for six minutes, or the amount of data that can be transferred is 2.25 megabytes (MB). If a 10MB file has to be transferred, terminal 205 may decide to wait before submitting the file to the network. When terminal 205 moves within reach of micro-cell base station 220, it may reduce the transmit power of terminal 205 to 10mW. The current drain to
20 support a 50 kb/s GPRS uplink connection then becomes 10mA. As a result, the battery level is sufficient to support the transfer of a 22.5MB file and more than sufficient to send the 10MB file to the network.

Figure 3 depicts a cordless phone system including battery management according to the present invention. Cordless system 300 is shown with base
25 station 310 and voice terminal 320. Air interface 340 supports different voice coding schemes ranging from 64 kb/s Pulse Code Modulation (PCM) to 4 kb/s Code Excited Linear Prediction (CELP). In this example, the battery is a 600 milli-ampere-hour (mAh) battery which is 10% charged (60 mAh). For the 64 kb/s transmit mode, the terminal drains 100 mA whereas for the low rate 4 kb/s
30 transmit mode, the current drain is only 10 mA. When a call is made, initially the

64 kb/s mode is used for perfect speech quality. However, the perfect speech quality mode can only be sustained for 36 minutes before the battery is empty. Talk time may be extended by switching to a lower (but lower quality) rate by gradually reducing the transmission rate (say from 64 kb/s to 32, to 16, 8 and 4 kb/s). For instance, terminal 320 only has 64 kb/s and 4 kb/s modes. If after 30 minutes in the 64 kb/s mode the connection is still on, the system may switch to the 4 kb/s mode for the uplink. Instead of having 6 minutes left, the phone can be used for another hour albeit with a lower speech quality in the uplink.

Figure 4 illustrates a timing diagram of parameters encountered in cordless phone operation as depicted in Figure 3. In Figure 4, the events in time are shown. When the battery is only 1.7% charged, it switches to a mode with less current drain. As part of the connection setup, the terminal may communicate the following record to the base station (values in the table below are given as example):

current battery level	60mAh
power drain 64 kb/s mode	100mA
power drain 4 kb/s mode	10mA

15

Base station 310 may then decide when to switch modes in order to extend the service time at the expense of the voice quality.

Figure 5 depicts a remote sensor system with battery management according to the present invention. A wireless telemetry system 500 is shown which includes central master 510 that connects to sensors 520a-e distributed in a manufacturing hall. A battery is connected to each one of sensors 520a-e to provide operating power. Periodically, central master 510 wirelessly activates sensors 520a-e to retrieve some readings like temperature, humidity, and so on. In addition to these reading, sensors 520a-e report battery status. If one of the sensors reports a low battery, central master 510 can activate another sensor to take over the operation of first sensor. Additionally, central master 510 can signal

25

or alarm a unit to be checked by maintenance. Maintenance can then replace the battery of the considered sensor before the sensor has lost contact with central master 510.

Figure 6 illustrates a Bluetooth connection between a Personal Computer (PC) and a Personal Digital Assistant (PDA) with battery management, according to the present invention. PC 610 and PDA 620 are shown as being in contact with each other via Bluetooth link 660. When coming into each other's range, PC 610 and PDA 620 try to synchronize a mailbox. PC 610 is permanently connected to network 650 and has received many new mail items. To prevent aborting data exchange in the middle of synchronization because of a depleted battery in PDA 620, PC 610 first checks battery status of PDA 620 by requesting a battery status report from PDA 620 via Bluetooth link 660. Additionally, PDA 620 may indicate its power drain when supporting a Bluetooth connection. If the battery is okay, synchronization can commence. If the battery is too low to support the entire synchronization session, PC 610 may choose not to start synchronization, but instead send a message to PDA 620 that the PC 610 battery is too low to support this synchronization service (although it may be high enough to support some other, less demanding functions). Alternatively, battery status may be sufficient just to send the headers and subject fields of the Email messages but not the bodies and attachments.

Figure 7 depicts a Bluetooth connection between a mobile phone and a paired headset with battery management, according to the present invention. Mobile phone 720 and a headset 710 is connected via Bluetooth link 750. Mobile phone 720 is wirelessly connected to a mobile network (not shown) via cellular link 760 and is locked to base station 730. The battery of headset 710 is 10% charged. This level may be enough to support a voice connection for 30 minutes. However, if MP3 audio files are to be transmitted to headset 710, only 5 minutes can be supported in the headset. Depending on the service requested by the user, mobile phone 720 may deny services because of a low battery level in headset 710. Alternatively, the display in mobile phone 720 may show the battery

level of headset 710 in addition to the mobile phone 720 battery level. In that case, headset 710 reports battery status periodically to mobile phone 720. In a wireless personal area network established with Bluetooth, the status of all the batteries in the network can be communicated between all units in the network.

5 This information can be displayed on each unit, but can also be used to schedule traffic flows and make decisions which modes are most appropriate to serve the user in an optimal way.

Power drain in similar devices will differ from manufacturer to manufacturer. Power drain information can be downloaded or flashed into the terminal (if transmit power control is applied, a look-up table may be used with

10 different entries for different transmit power levels). Alternatively, the terminal can learn automatically while in service what the drain per mode will be. All the information like transmit battery status (change), transmit power level, operational mode, and duration of operation can be communicated to the operating system of the terminal. From this information, the terminal can derive the power drain for

15 each operation.

Figure 8 illustrates a method for managing a communication device power source in a network according to a preferred embodiment of the present invention. The process begins at step 805, which depicts connecting, or

20 activating, a communications device to a network. The communications device may be a mobile phone in a wireless network, a cordless phone set connected to a PSTN, a remote battery powered sensor, a Personal Digital Assistant connected to a network through a computer, a mobile phone and Bluetooth headset connected to a wireless network, or any other equivalent device and

25 network.

For the purpose of explanation and description the communication device will be a mobile phone connected to a wireless network and the power supply is the mobile phone battery. When connecting to a network (Step 810) a controller may query the mobile phone to determine the parameters regarding the power

30 level of the mobile phone's battery and the power consumption of the services to

which the mobile phone may be subscribed. (Step 815) If the phone is reconnecting to the network, the parameters may already be stored and the controller then retrieves the parameters to apply to any transactions that take place between the phone and the network (Step 820). The phone is monitored for
5 any data transfers that may take place between the phone and the network (Step 825).

If a data transfer is scheduled or requested, the size of the data to be transferred is determined. In the case of a voice transmission, the controller determines the battery power level and sets the appropriate quality of service
10 (QoS). The power level is monitored and the QoS is adjusted to accommodate the remaining power in the battery. This determination may be made by the network controller or by the phone (Step 830). The current power drain of the battery for the phone and the amount of remaining power is calculated. The amount of data to be transferred and the power drain relating to the type and
15 amount of data to be transferred is also determined. The amount of power required to transfer the data is then calculated (Step 835).

A determination is then made whether the battery power level is sufficient to make the complete data transfer (Step 840). If so, the data transfer is commenced (Step 845). If not, a determination is then made if a portion of the
20 data can be transferred (Step 850). If the data can be divided, a portion is sent to the phone and the remainder is then sent to a predetermined destination. An automatic message is also sent to the device indicating the actions taken and the address that the phone may access to retrieve the balance of the message (Step 855).

25 If the determination is made that the data either cannot be divided or the battery power level cannot support a complete transfer, the complete message may be re-directed to a predetermined destination and an automatic message is then sent to the device (step 860).

As will be recognized by those skilled in the art, the innovative concepts
30 described in the present application can be modified and varied over a wide

range of applications without departing from the spirit and scope of the invention in its broadest form. Accordingly, the scope of patented subject matter should not be limited to any of the specific exemplary teachings discussed, but is instead defined by the following claims.

WHAT IS CLAIMED IS:

1. A method for managing traffic in a network, involving a communication
5 device with a limited power supply, characterized by:
 - determining a current level of available power in said power supply for transmitting and receiving functions of said communication device;
 - communicating said power level to a controller;
 - determining a current power drain rate of said power source;
 - 10 detecting a need for data transfer associated with said communication device, wherein said data transfer is one of an incoming call to said communication device and a request for transmission from said communication device;
 - determining a quantity of data relating to said data transfer;
 - 15 calculating whether said power level is sufficient to effect the transfer of said data; and
 - signaling said controller to effect said data transfer according to said power level calculations.
- 20 2. The method of Claim 1, further characterized by:
 - storing initial parameters for said power supply of said communication device and periodically updating said power supply parameters, wherein said parameters include:
 - a drain rate for each communication service available to said
 - 25 communication device; and
 - an initial power source level upon connection to the network.
3. The method of Claim 1, wherein said step of signaling said controller comprises instructions based on said power supply connections for one of
30 receiving all of said data, redirecting all of said data to a predetermined location,

-20-

and receiving a portion of said data and directing the remainder of said data to a predetermined address.

4. The method of Claim 1, wherein said communication device is a battery
5 operated remote sensor and said network is a wireless network.

5. The method of Claim 4, wherein said network is a non-wireless network.

6. The method of Claim 1, wherein said communication device is a wireless
10 mobile terminal and said network is a wireless network.

7. The method of Claim 6, wherein said traffic is voice traffic and a voice call
is begun on said mobile terminal at a first quality of service level according to an
initially determined power level and power drain rate of said mobile terminal
15 battery, and said voice call is continued at a second quality of service level
according to a subsequently determined power level and power drain rate of said
mobile terminal battery.

8. The method of Claim 6, wherein a video message is presented for transfer
20 and the audio portion of the message is transferred but the video portion is
redirected to a predetermined address and a message is sent to inform the
recipient of said audio the location of said video portion.

9. The method of Claim 3, wherein said data comprises a Multimedia
25 Messaging Service (MMS) message.

10. The method of Claim 3, wherein said data comprises a video message.

11. The method of Claim 1, wherein said communication device is a wireless
30 modem.

12. The method of Claim 1, wherein said communication device is a cordless phone system and said network is a public switched telephone network (PSTN).
- 5 13. The method of Claim 1, wherein said communication device is a personal digital assistant and connects to a PSTN by wirelessly connecting to a computer connected to said PSTN
14. An apparatus for managing traffic in a network involving a communication
10 device with a limited power supply, characterized by:
a transceiver for receiving and transmitting messages;
a controller for monitoring a current power level of said power supply and a calculated power drain rate of said communication device;
means coupled to said power supply for determining said power drain rate
15 of said communication device; and
signal means for signaling said communication device to one of receive and transmit messages according to said current power level and said drain rate.
15. The apparatus of Claim 14, further characterized by:
20 a database for storing initial parameters for said power supply of said communication device and periodically updating said power supply parameters, wherein said parameters include:
a drain rate for each communication service available to said communication device; and
25 an initial power source level upon connection to the network.
16. The apparatus of Claim 14, further characterized by
means for signaling said controller to one of: receiving all of said data, redirecting all of said data to a predetermined location, and receiving a portion of

-22-

said data and directing the remainder of said data to a predetermined address based on said power supply measurements.

17. The apparatus of Claim 14, wherein said communication device is a battery operated remote sensor and said network is a wireless network.

18. The apparatus of Claim 17, wherein said network is a non-wireless network.

19. The apparatus of Claim 14, wherein said communication device is a wireless mobile terminal and said network is a wireless network.

20. The apparatus of Claim 19, wherein said traffic is voice traffic and a voice call is begun by said wireless mobile terminal at a first quality of service level according to an initially determined power level and power drain rate of a battery for said wireless terminal and said voice call is continued at a second quality of service level according to a subsequently determined power level and power drain rate of said battery.

21. The apparatus of Claim 14, wherein a video message is presented for transfer and the audio portion of the message is transferred but the video portion is redirected to a predetermined address and a message is sent to inform the recipient of said audio the location of said video portion.

22. The apparatus of Claim 14 wherein said communication device is a wireless modem.

23. The apparatus of Claim 14, wherein said communication device is a cordless phone system and said network is a public switched telephone network (PSTN).

24. The apparatus of Claim 14, wherein said communication device is a personal digital assistant and connects to a PSTN by wirelessly connecting to a computer connected to said PSTN

5

25. The apparatus of Claim 14, wherein said means for determining said power drain rate further comprises periodically determining said power drain rate associated with said communication device when said communication device changes location during data transmission.

10

26. The method of Claim 1, wherein the step of determining a current power drain rate of said power source further comprises the step of periodically determining said drain rate when said communication device changes location during data transmission.

1/6




FIGURE 1
(Prior Art)

2/6




FIGURE 2

3/6




FIGURE 3

4/6




FIGURE 4




FIGURE 5

5/6




FIGURE 6




FIGURE 7

6/6




FIGURE 8

INTERNATIONAL SEARCH REPORT

International Application No

PCT/IB 03/01155

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 H04M1/73 H04Q7/32

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 H04M H04Q H04B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	GB 2 366 134 A (NOKIA MOBILE PHONES LTD) 27 February 2002 (2002-02-27) page 2, line 6 - line 20 page 3, line 10 - line 16 page 7, line 16 - page 8, line 28 abstract; claims 1-7,13-17; figure 4	1-6, 8-19, 21-26
Y	--- -/--	7,20

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

9 September 2003

Date of mailing of the international search report

30. 09. 2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

TOMAS WÄSSINGBO/JAA

INTERNATIONAL SEARCH REPORT

International Application No

PCT/IB 03/01155

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 2001/011032 A1 (SUZUKI TAKAHIRO) 2 August 2001 (2001-08-02) paragraph [0004] paragraph [0008] paragraph [0014] paragraph [0033] paragraph [0036] - paragraph [0037] paragraph [0060] abstract; claims 1,4,7,12; figure 2	1-6, 8-19, 21-26
Y	---	7,20
X	EP 1 032 230 A (SONY CORP) 30 August 2000 (2000-08-30) paragraph [0003] - paragraph [0004] paragraph [0023] abstract; claim 1; figure 3 ---	1,14
X	US 2001/012774 A1 (MURAMATSU TOSHIHIKO) 9 August 2001 (2001-08-09) paragraph [0005] paragraph [0008] - paragraph [0009] paragraph [0017] - paragraph [0019] paragraph [0026] paragraph [0028] paragraph [0047] abstract; claims 1,2,8,10,12-14,19-22 ---	1,14
Y	WO 99 43105 A (QUALCOMM INC) 26 August 1999 (1999-08-26) page 11, line 18 - line 22 -----	7,20

INTERNATIONAL SEARCH REPORT

International Application No

PCT/IB 03/01155

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
GB 2366134	A	27-02-2002	NONE	
US 2001011032	A1	02-08-2001	JP 2001217927 A CN 1307424 A GB 2365271 A	10-08-2001 08-08-2001 13-02-2002
EP 1032230	A	30-08-2000	JP 2000253010 A CN 1266345 A EP 1032230 A2 US 6229990 B1	14-09-2000 13-09-2000 30-08-2000 08-05-2001
US 2001012774	A1	09-08-2001	JP 2001224068 A GB 2365273 A	17-08-2001 13-02-2002
WO 9943105	A	26-08-1999	US 6545989 B1 AU 2773099 A AU 2776099 A AU 3300899 A AU 747724 B2 AU 3300999 A BR 9904864 A BR 9904866 A CN 1256817 T CN 1262820 T EP 0992132 A1 EP 0976206 A1 EP 0983643 A1 EP 1004217 A1 FI 992212 A FI 992247 A JP 2002503429 T JP 2001522574 T NO 995079 A NO 995080 A WO 9943180 A1 WO 9943100 A1 WO 9943105 A1 WO 9943101 A1 US 6421540 B1 US 2003100298 A1 US 6366778 B1	08-04-2003 06-09-1999 06-09-1999 06-09-1999 23-05-2002 06-09-1999 16-10-2001 26-09-2000 14-06-2000 09-08-2000 12-04-2000 02-02-2000 08-03-2000 31-05-2000 17-12-1999 17-12-1999 29-01-2002 13-11-2001 16-12-1999 16-12-1999 26-08-1999 26-08-1999 26-08-1999 26-08-1999 16-07-2002 29-05-2003 02-04-2002